234 5678



### IT PRODUCTS

### KVM Switches/Dual Access/KVM Booster Products

KVM Switch Milestone's 'SERVER SHARER' ML 201/401/801/1601SS is a devices that enables one person to operate 2/4/8/16 Servers Cascadable up to 256 servers on single set of monitors (VGA), keyboard, mouse. (PS-2 & USB).

#### MODELS AVAILABLE:

For PS/2 Servers: • ML 201 SSPL

ML 201 SS

ML 401 SSPL

MI 401 SS

MI 801 SS

MI 401 SSRM

ML 801 SSRM

ML 1601 SSRM

For USB Servers: • ML 201 SSUPL • ML 201 SSU

MI 401 SSU

MI 801 SSU

ML 401 SSURM
 ML 801 SSURM
 ML 1601 SSURM

Dual Access System > Milestone's "DUAL ACCESS SYSTEM" ML102KVM is a device that helps two people to share a single PC with an additional Monitor (VGA), Keyboard & Mouse in auto as well as manual mode.

MODELS AVAILABLE: • ML - 102 KVM

KVM Booster > Milestone's "KVM BOOSTER" ML101 KVM is a device that boosts Keyboard, Monitors (VGA) and Mouse single upto a distance of 30 Mtrs.

MODELS AVAILABLE: • ML - 101 KVM



# Training Net Products

Training Net > Teach your students theory & practical at the same time using Milestone's training net. No Software Required, No Slowing down of PC, Cascadable for 200 Nos. Of Nodes.

MODELS AVAILABLE: • ML 105 T. Net • ML 108 T. Net • ML 110 T. Net • ML 112 T. Net

## Data Switches/Serial to Parallel Convertor Products

Data Switch Milestone's "Data Switch" is a sophisticated printer sharer used in a modern office where many computers share printer to save office space & investment on printers or plotters.

#### **MODELS AVAILABLE:**

For Parallel / Bitronics Port: • ML 201 APL

For Serial Port:

ML 102 MPLB
 ML 401 A/M

ML 801 A/M

ML 202 M

• ML 401 A/M B

ML 201 MEC
 ML 201 A/M S
 ML 401 S A/M
 ML 801 S A/M

USB Data Switch > Milestone's "USB Data Switch" is used to connect computers and/or peripherals having USB interface.

MODELS AVAILABLE: • ML 201 USB • ML 401 USB • ML 801 USB

Serial/Parallel Convertor > It is a bi-directional convertor useful to convert serial (RS232C) to parallel (Centronics) or parallel (Centronics) to serial (RS232C) interface with selected Baud rate (300-19.2 K) and direction.

MODELS AVAILABLE: • ML SP - 1





## **GPRS Splitter Products**

GPRS Splitter > This is a devices to connect 1 GPRS input to 4/8 GPRS outputs. These are device used to connect 1 Serial Port input to many buffered simultaneous Serial Port output.

#### MODELS AVAILABLE:

For RS232 to RS232:

ML 104 GPRS
 ML 108 GPRS
 ML 116 GPRS

For RS232 to RS485:

• ML 104 U

• ML 108 U

ML 116 U

For RS232 to RS232/RS485: • ML 1044 U

For RS485 to RS232/RS485: • ML A 104 U • ML A 108 U ML A 1044 U



### INDUSTRIAL PRODUCTS

## RS232/RS422/RS485/USB/IP Convertor

RS232 to RS422 Convertor Milestone's "RS232 to RS485/RS422 Converters" are designed for high speed data transmission between computer system and or peripherals over long distance under noisy conditions and having Isolation and Surge Protection on RS485 output.

MODELS AVAILABLE: • LD - 15U • LD - 15 • LD - 15 PL • LD - 15 PN • LD - 15 UA

RS232 to RS485 Splitter > These are device used to connect one serial RS232 input to 4/8/16 buffered simultaneous RS485 outputs.

MODELS AVAILABLE: • ML LD - 104 U • ML LD - 108 U • ML LD - 116 U

USB to Serial Convertor ▶ Milestone's "USB to Serial Converter" is a powerless compact device which converts USB input from PC to serial output (RS232). It Supports all Signals of RS232C.

MODELS AVAILABLE: • ML UD - 35U

USB to RS232 Distributor ▶ It is a device to connect 4/8 Serial Port (RS232) to a single USB port. It Creates 4/8 Virtual independent COM ports on the PC

MODELS AVAILABLE: • ML 104 US • ML 108 US.

USB or RS232 to RS485/RS422 Convertor ▶ Milestone's "USB to RS485/RS422 Convertor" is a device which converts USB or RS232 input to RS232/RS485/RS422 Output.

MODELS AVAILABLE: • ML UD - 25U

Ethernet (IP) to RS232 Convertor ▶ Milestone's "Ethernet to RS232 Convertor" is a device which converts Ethernet (IP) input to RS232 Output. It has optical isolation and surge protection.

MODELS AVAILABLE: • ML IP - 35U.

Ethernet (IP) to RS422/RS485 Convertor Milestone's "Ethernet to RS422/RS485 Convertor" is a device which converts Ethernet (IP) input to RS422/RS485 Output.It has optical isolation and surge protection.

MODELS AVAILABLE: • ML IP-25U

RS485 (2 wired) to RS422/RS485 (4 wired) Convertor Milestone's "RS485 (2 wired) to RS422/RS485 (4 wired) Convertor" It Converts 2 wired RS485 ports input to 4 wired RS422/RS485 output and vice versa, it also works as RS422/RS485 repeater.

MODELS AVAILABLE: • ML LD -15 UCR

RS232 to Current Loop Convertor > It is a bi-directional converter useful to convert RS232 to 0-20 mA current loop and vice versa.

MODELS AVAILABLE: • LD - 1C





# Repeater/Isolator/Surge Protector/Line Driver

RS422/RS485 Repeater/Isolator Milestone's "RS422/RS485 Repeater / Isolator" is a device which isolates the input and output connection of RS422/RS485 interface and increases the drive capability.

MODELS AVAILABLE: • LD15 UR

RS232 Isolator Milestone's "RS232 Isolator" is a device which isolates the input and output connection of RS232C interface with no ground in common.

MODELS AVAILABLE: • ML LD - 14I

Surge Protector • [Parallel / Serial (RS232C) / RS422 / RS485] Protect your parallel / RS232C / RS422C / RS485 data lines from unexpected surges and ground spikes.

MODELS AVAILABLE: • SP2 51 • SP2 52 • Sp2 53 • SP2 54 • ML SP - 25

Line Driver Milestone's "Line Driver" are ideal accessories providing low cost, high speed for connecting computers & Peripherals on Serial RS232 ports spread around a distance of 20 kms.

MODELS AVAILABLE : • LD - 12A / LD - 22A • LD - 14A / LD - 24A