



OPERATING MANUAL
FOR
HDMI EDID FEEDER
ML-EDID-FD

Milestone Electronics Pvt. Ltd.

HDMI EDID FEEDER

HDMI EDID FEEDER by Milestone is a device that helps person to manage & control the EDID information between HDMI source & HDMI display.

Features

INSTALLATION	Easy to install - plug and play kind. <ul style="list-style-type: none">● HDTV Compatible● Can work with DVI inputs & outputs
SHARING	1 HDMI Input, 1 HDMI Output
COMPATIBILITY	Fully compatible to HDMI Ports.
INDICATION	LED indication for Power.
HDMI RESOLUTION	Support 4K with EDID setting-4K@30Hz, pass through -4K@60Hz
COMPLIANCE	HDCP, CEC Support
AUDIO FORMAT	2 CH □ LPCM 2.0 5.1CH□ LPCM, Dolby-AC3, DTS 5.1 HD Mode□ Highest Audio format
HDMI CABLE LENGTH	5M on both side

SPECIFICATIONS

MODEL	ML-EDID-FD
INPUT /OUTPUT CONNECTORS	HDMI × 2
EDID ROTATE BUTTON	1
LED INDICATION	PWR
MAINS INPUT (DC) ADAPTOR	Self-Power
DIMENSION TABLE TOP	52mm X 45mm X 22mm
WEIGHT	50 g

EDID SETTING: -

16 EDID SETTINGS	
A- 4K@30,2CH	I- 1080,3D, HD
B- 4K@30,5.1CH	J- 1080I,2CH
C- 4K@30, HD	K- 1080I, 1CH
D- 1080P,2CH	L- 1080I, HD
E- 1080P,5.1CH	M- 720P,2CH
F- 1080P, HD	N- 720P,5.1CH
G- 1080P,3D,2CH	O- 720P, HD
H- 1080P,3D,5.1CH	P- SINK EDID

OPERATION: -

- 1) Connect 1 HDMI cable to source & other to EDID FEEDER unit at any HDMI Input/Output port.
- 2) Connect 1 HDMI cable from other HDMI Input/Output port of EDID FEEDER to display like TV, Projector etc.
- 3) Adjust EDID as per requirement by rotating EDID button.

